

DT72



STANDARD FEATURES

High Torque Drive system
 Extreme Gradeability - market leading
 Rear Oriented Boom position
 Auto Levelling Basket
 Maximum Approach Angle - market leading
 OSHA and ANSI 92.20 Standards certified
 High Pressure Water/Air connection to Basket
 Automatic Stabilization
 Negative Working Height - market leading
 Remote Management and Diagnostic software
 Up & Over - market leading
 Invisible Boom

ADDITIONAL/OPTIONAL FEATURES

Brushes for Boom protection
 Optional 1 Man Basket
 Optional Cages
 Optional Crane Hook
 16' Wire Control, control at ground
 Radio Control
 Auto-close Functionality

Custom Paint Options available (Upper and Lower sections)
 Electro pump 110V
 Cage for materials handling
 Extra Large Basket
 Fiberglass Basket
 Hook & Crane certification



TECHNICAL SPECIFICATIONS

MEASUREMENTS

A	Stowed Height with basket	7' 6"
B	Overall Length with basket	22' 11"
C	Overall Width with outrigger closed	6' 11"
D	Stowed Height without basket	7' 6"
E	Overall Length without basket	20' 11"
	Overall Width with outrigger open	7' 3"
	Length outrigger footprint	12'

Total weight 12694 lbs

PERFORMANCE

Platform working height (max)	71' 9"
Horizontal outreach (max)	29' 6"
Negative work	- 6' 7"
Up & over clearance	45' 11"
Basket Capacity	507 lbs
Hook Capacity	573 lbs
Basket rotation	180°
Turret rotation	720°
Maximum approach angle	23 °
Longitudinal maximum gradient of the ground	7 %
Lateral maximum gradient of the ground	9 %
Standard power source	Diesel
Optional power source	Electro pump



